




1 DOOR SILL 3"



2 DOOR SILL @ TRANSITION 3"



3 DOOR SILL @ FIN. CONC FL. 3"



4 DOOR FRAME 3"


## ROOM FINISH SCHEDULE

ROOM NUMBER	ROOM TITLE	FLOOR	BASE	WALLS				WAINSCOT				CEILING	REMARKS
				NORTH	EAST	SOUTH	WEST	NORTH	EAST	SOUTH	WEST		
01	OFFICE	F-6	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
02	SERVICE	F-2	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
03	BREAKROOM	F-6	B-1	WM-2	WM-1	WM-1	WM-1					C-1	
04	JANITOR	F-7	B-5	WM-2	WM-2	WM-1	WM-1					C-2	
05	RESTROOM	F-7	B-6	WM-2	WM-2	WM-2	WM-2					C-2	
06	HALLWAY	F-7	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
07	STORAGE	F-7	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
08	WAITING	F-6	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
09	ENTRY	F-6	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
10	SALES	F-6	B-1	WM-1	WM-1	WM-1	WM-1					C-1	
11	ENTRY	F-6	B-1	WM-1	WM-1	WM-1	WM-1					C-1	

## MATERIAL SCHEDULE

F-1	COMM. SHEET VINYL (ARMSTRONG 86526 OYSTER)
F-2	CARPET
F-3	8x8 QUARRY TILE
F-4	SEALED CONCRETE (2 PART, WATER BASED, EPOXY CONCRETE FLOOR FINISH)
F-5	(VERIFY W/OWNER COLOR & STYLE PRIOR TO CONSTRUCTION)
F-6	EXISTING FLOOR TO REMAIN
F-7	12" x 12" CERAMIC TILE, COLOR & STYLE BY OWNER
B-1	4" RUBBER TOP SET BASE
B-2	6" COVE ROUND TOP BASE (TO MATCH FLOOR)
B-3	COMMERCIAL SHEET VINYL 6" UP WALL W/ MIN. 3/8" RADIUS COVE
B-4	QUARRY TILE 6" UP WALL W/ MIN. 3/8" RADIUS COVE
B-5	CERAMIC TILE 6" UP WALL W/ MIN. 3/8" RADIUS COVE
WM-1	1/2" GYP. BOARD ON STUDS
WM-2	5/8" W-R GYP. BOARD ON STUDS WHERE REQUIRED PER U.B.C. REQUIREMENTS
WM-3	5/8" TYPE "X" FIRE RATED GYP BOARD
WF-1	PAINT 2 COATS (COLOR BY OWNER)
WF-2	TAPE & FINISH FOR APPLICATION OR WALL COVERING. OWNER TO PROVIDE SIZING MATERIALS & INSTALLATION.
WF-3	TAPE & TEXTURE, 2 COATS OF PAINT (COLOR BY OWNER)
WF-4	(FRP) FIBER GLASS REINF. PANELS
WF-5	N/A
WF-6	N/A
WF-7	CERAMIC TILE FULL HT.(VERIFY W/OWNER COLOR & STYLE PRIOR TO CONSTRUCTION) 1/8" GROUT JOINT
WA-1	F.R.P. FULL HT.
C-1	5/8" x 24" x 48" CLASS "A" MINERAL BOARD WHITE FISSURED FINISH (OMNI ILLUSION TWO/24 PANELS USG3575)
C-2	5/8" GYP. BOARD ON CEILING OVER STUDS
C-3	OPEN TO STRUCTURE ABOVE
C-4	VINYL COVERED GYP. BOARD IN "TEE" BAR SUSP. CEILING
C-5	REGULAR 24"x24" ARMSTRONG SECOND LOOK II 2767 WHITE SEE NOTE #2
C-6	5/8" TYPE "X" FIRE RATED GYP BOARD (2 LAYERS)

NOTES: (VERIFY WITH OWNER ALL MATERIALS COLORS & FINISHES PRIOR TO CONSTRUCTION)



05 RESTROOM

SCALE: 1/8" = 1'-0"


## DOOR SCHEDULE

NOTES	KEY SCHEDULE	DOOR NUMBER	ROOM NUMBER	DOOR TYPE	SIZE		DOOR MATERIAL	DOOR FINISH	DETAILS			LOUVERS SIZE	HARDWARE GROUP	FIRE RATING	REMARKS
					WIDTH	HEIGHT			HEAD	JAMB	SILL				
		1	11	CC	6'-0"	7'-0"	AL	SEE NOTES	PER	MFG	SPECS				
		2	01	B	3'-0"	7'-0"	HC	SEE NOTES							
		3	01	B	3'-0"	7'-0"	HC	SEE NOTES							
		4	03	B	3'-0"	7'-0"	HC	SEE NOTES							
		5	04	B	3'-0"	7'-0"	HC	SEE NOTES							
		6	05	A	3'-0"	7'-0"	HC	SEE NOTES							
		7	07	B	3'-0"	7'-0"	HC	SEE NOTES							

## WINDOW TYPES & NOTES

- 1 1/4" TEMPERED GLASS
- REFER TO FLOOR PLAN, ELEVATIONS AND WALL SECTIONS FOR ROUGH OPENING DIMENSIONS.
  - ALL STOREFRONT MATERIAL AND GLAZING SHALL BE SUPPLIED AND INSTALLED BY G.C. U.O.N.
  - STOREFRONT FRAMES SHALL BE CLEAR ANODIZED.
- 2 1/4" TEMPERED GLASS
- REFER TO FLOOR PLAN, ELEVATIONS AND WALL SECTIONS FOR ROUGH OPENING DIMENSIONS.
  - ALL STOREFRONT MATERIAL AND GLAZING SHALL BE SUPPLIED AND INSTALLED BY G.C. U.O.N.
  - STOREFRONT FRAMES SHALL BE CLEAR ANODIZED.

## DOOR TYPES



## HARDWARE GROUPS

SET "A"	SET "E"
1 1/2 PR BUTTS	1 1/2 PR BUTTS / NRP
1 LOCK SET/LEVER	1 LOCK SET/LEVER
1 DOOR STOP	1 DOOR STOP
	1 THRESHOLD
	1 WEATHER STRIP
	1 CLOSER
SET "B"	SET "F"
1 1/2 PR SPRING	2 1/2 PR BUTTS
1 LOCK'G HINGES	2 PUSH PLATE
1 DOOR STOP/LEVER	4 KICK PLATE
SET "C"	SET "G"
1 1/2 PR SPRING HINGES	1 1/2 PR BUTTS / NRP
1 LOCK SET/LEVER	1 LOCK SET/LEVER
1 DOOR STOP	1 DOOR STOP
1 HANDICAP SIGN (SEE 9/HC-1)	1 THRESHOLD
1 CLOSER	1 WEATHER STRIP
SET "D"	1 CLOSER
1 1/2 PR BUTTS / NRP	SET "H"
1 LOCK SET	1 1/2 PR BUTTS / NRP
1 DOOR STOP	1 DOOR STOP
3 SILENCERS PER DOOR	1 THRESHOLD
1 THRESHOLD	1 WEATHER STRIP
1 WEATHER STRIP	1 PANIC HARDWARE
	1 CLOSER

VERIFY ALL FINISHES & MATERIALS W/ OWNER PRIOR TO PURCHASE & INSTALLATION

## DOOR NOTES

- ALL DOORS 1-3/4" THICK UNLESS OTHERWISE NOTED
- DOOR CONSTRUCTION  
SC = SOLID WOOD CORE STAIN GRADE (SELECT BIRCH)  
HC = HOLLOW WOOD CORE STAIN GRADE  
AL = ALUMINIUM FACTORY ANODIZED CLEAR  
MTL = HOLLOW METAL DOOR & FRAME  
HOLLOW METAL DOORS 18 GA & HOLLOW METAL FRAMES 16 GA
- TYPICAL DOOR FRAME FINISH  
HOLLOW METAL = FACTORY FINISH  
ALUMINIUM = FACTORY CLEAR ANODIZED
- 1/3, 3/4, 1, 1-1/2 ETC. INDICATES HOURS OF FIRE RATING
- UNDERCUT ALL DOORS 5/8" TYPICAL UON
- WALL MOUNTED DOOR STOP

## RESTROOM ACCESSORY SCHEDULE

- A 42" OR 36" GRAB BARS BOBRICK #B4937 OR EQUAL
- B TOILET PAPER HOLDER
- C TOILET SEAT COVER DISPENSER
- D PAPER TOWEL DISPENSER/GARBAGE DISPOSAL UNIT (BUILT-IN)
- E SOAP DISPENSER
- F 24" x 36" POLISHED MIRROR W/ NAT. ALUMINUM TRIM

SEE DETAIL 7/HC-1 FOR RESTROOM ACCESSORY LOCATIONS  
WRAP HOT WATER AND DRAIN LINE  
PER CODE REQUIREMENTS SEE 5/HC-1