


NORLAKE WALK-IN 5' X 6', 6' X 6', 6' X 8' OR 8' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL

NOTE: KLB = REFRIGERATOR, KLF = FREEZER.

MODEL #	A	B	C	D	E	F	G	INTERIOR CU. FT.	VOLTS/HZ/PH	MINIMUM CIRCUIT AMPS	TOTAL SYSTEM AMPS	MAXIMUM FUSE SIZE
KLB45-CX-SUB	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	115/60/1	14.2	11.7	20
KLB46-CX-SUB	4' (121.9cm)	5' (152.4cm)	26" (66cm)	59" (149.9cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	115/60/1	14.2	11.7	20
KL856-CX-SUB	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KL866-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	10.5	8.7	15
KL868-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KL8683-CX-SUB	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	11.9	10	15
KL87446-CX-SUB	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KL87466-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	11.9	10	15
KL87468-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KL874683-CX-SUB	6' (182.9cm)	243.8cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	10	15
KL87746-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	123	115/60/1	14.2	11.7	20
KL87756-CX-SUB	5' (152.4cm)	182.9cm	26" (66cm)	78" (198.1cm)	26" (66cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	137	115/60/1	14.2	11.7	20
KL87766-CX-SUB	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	10.5	8.7	15
KL87768-CX-SUB *	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KL877683-CX-SUB *	6' (182.9cm)	243.8cm	26" (66cm)	78" (198.1cm)	37" (94cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	270	208-230/60/1	11.9	8.7	15
KLF45-Cx	4' (121.9cm)	152.4cm	26" (66cm)	59" (149.9cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	77	208-230/60/1	13.4 13.4 DEFROST	10.7	20
KLF46-Cx	4' (121.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	44 1/2" (113cm)	14 7/8" (37.7cm)	105	208-230/60/1	13.4 13.4 DEFROST	10.7	20
KLF56-Cx	5' (152.4cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF68-CX *	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	168	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF68-CX *	6' (182.9cm)	182.9cm	26" (66cm)	66" (167.6cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KLF683-CX	6' (182.9cm)	243.8cm	26" (66cm)	66" (167.6cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	231	208-230/60/1	10.8 DEFROST	9.1	15
KL87746-CX *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	123	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KL87756-Cx	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	137	208-230/60/1	13.4 13.4 DEFROST	9.1	15
KL87766-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	196	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KL87768-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KL877683-CX	6' (182.9cm)	243.8cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	270	208-230/60/1	10.8 DEFROST	9.1	15
KLF7846-CX *	4' (121.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	113	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7856-Cx	5' (152.4cm)	182.9cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	149	208-230/60/1	10.8 DEFROST	9.1	15
KLF7866-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	39" (99.1cm)	48 1/4" (122.6cm)	14 7/8" (37.7cm)	184	208-230/60/1	13.4 13.4 DEFROST	8.2	15
KLF7868-CX	6' (182.9cm)	182.9cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15
KLF78683-CX	6' (182.9cm)	243.8cm	26" (66cm)	78" (198.1cm)	36 1/2" (92.7cm)	59" (149.9cm)	22 7/8" (58.1cm)	256	208-230/60/1	10.8 DEFROST	9.1	15

MODEL: CA33-RR12

ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" X 26")
OR 24 HALF SIZE PANS (13" X 18")
NSF APPROVED

LOCKWOOD DECK RETARDER

MODEL: CA27-RR12

ALUMINUM WELDED CONSTRUCTION
HOLDS 12 FULL SIZE PANS (18" X 26")
OR 24 HALF SIZE PANS (13" X 18")
NSF APPROVED


LOCKWOOD REACH-IN RETARDER

NOTE: CASH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. THESE SYSTEMS HAVE FOR MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL, MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. UL LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.


MANUFACTURER CLEARANCE SPECIFICATIONS:

DO NOT STORE BOXES ON THE TOP OF COOLER OR FREEZER. STORED OBJECTS WILL OBSTRUCT AIR FLOW AND CAUSE VENTILATION PROBLEMS FOR THE REFRIGERATION SYSTEMS.

24\"/>



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL

THREE COMPARTMENT CORNER SINKS ALSO AVAILABLE.
 1/2" NPT WATER LINES. 2" DRAINS.
 UL AND C-UL LISTED.

DUKE MANUFACTURING STAINLESS STEEL SINK

Diagram of a stainless steel sink. The overall width is 16 3/16" [41.1cm]. The depth is 21 1/2" [54.6cm]. The height of the sink body is 17 1/2" [44.4cm]. The mounting holes are spaced 16" [40.6cm] apart. The sink is labeled with model CA60-RR25 and a depth of 60" [152.4cm].

MODEL: CA60-RR25
 HOLDS 25 HALF SIZE PANS (13" X 18")

MODEL: CA76-RR33
 HOLDS 33 HALF SIZE PANS (13" X 18")

CA76-RR33 TO BE USED WITH 77 SERIES
 REFRIGERATOR.

ALUMINUM WELDED CONSTRUCTION
 NSF APPROVED

Diagram of a stainless steel shelving unit. The overall height is 74 5/8" [189.5cm]. The width is indicated as "SEE BELOW". The unit has five shelves and is labeled with model CA60-RR25.

AVAILABLE SIZES ARE:
 WIDTH: 14", 18", 21", 24"
 (35.6, 45.7, 53.3, 61cm)
 LENGTH: 24", 30", 36", 42", 48", 60" AND 72"
 (61, 76.2, 91.4, 106.7, 121.9, 152.4, 182.9cm)
 4 OR 5 TIER

DOCKWOOD RETARDER CABINET

INTERMETRO SHELVING SYSTEMS

Diagram of a Dockwood Retarder Cabinet. The overall height is 34" [86.4cm]. The width is 36" [91.4cm] to 120" [304.8cm] in 12" [30.5cm] increments. The cabinet is labeled with model CA60-RR25.

ELEVATION

Diagram of an Intermetro Shelving System. The overall height is 30" [76.2cm]. The unit has five shelves and is labeled with model CA60-RR25.


RIGHT END

NOTE: CASH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. THESE SYSTEMS HAVE FOR MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL, MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. UL LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.


MANUFACTURER CLEARANCE SPECIFICATIONS:

DO NOT STORE BOXES ON THE TOP OF COOLER OR FREEZER. STORED OBJECTS WILL OBSTRUCT AIR FLOW AND CAUSE VENTILATION PROBLEMS FOR THE REFRIGERATION SYSTEMS.

24\"/>



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL

Q-420 CUBER ON S-420 BIN
TYPE: AIR-COOLED, WATER-COOLED

ELECTRICAL SPECIFICATIONS

1 1/2/60/1 20 AMP FUSE MIN.
12.3 AMPS, WATER-COOLED = 1174 AMPS
WIRED DIRECT OR PER LOCAL CODE

220-240/50/1 ALSO AVAILABLE, SEE MANUFACTURER.

PLUMBING SPECIFICATIONS

3/8" (0.95cm) F.P.T. INLET, 1/2" (1.27cm) F.P.T. DRAIN

3/4" (1.91cm) BIN DRAIN

3/8" (0.95cm) F.P.T. WATER CONDENSER INLET (WATER-COOLED UNIT)
1/2" (1.27cm) F.P.T. WATER CONDENSER OUTLET (WATER-COOLED UNIT)

NSF APPROVED/U.L. #SA-4027/CSA LISTED

MANITOWOC ICE CUBER

G = WIDTH OF BODY

GEARE INTERCEPTOR

MANUFACTURER: ZURN INDUSTRIES

MODEL: Z1170

DIMENSIONAL DATA IN INCHES [mm]

SIZE	INLET/OUTLET SIZE	FLOW RATE C.F.M. [L-P.M.]	WATER GAL. [L]	CAPACITY GREASE LBS. [KG]	APPROX. WT. LBS. [KG]	C		D	
100*	2 [50]	4 [15]	3 [11]	8 [4]	42 [19]	10 [254]	7 [178]	10 [254]	7 [178]
200*		7 [26]	5 [19]	14 [6]	53 [24]	11 1/4 [286]	8 [178]	11 1/4 [286]	8 [178]
300*		10 [38]	6 [23]	20 [9]	66 [30]	11 3/4 [298]	8 [178]	11 3/4 [298]	8 [178]
400*	3 [75]	15 [57]	10 [38]	30 [14]	83 [38]	13 3/8 [340]	9 [178]	13 3/8 [340]	9 [178]
500		20 [76]	16 [60]	40 [18]	99 [45]	15 [381]	11 [254]	15 [381]	11 [254]
600		25 [94]	21 [79]	50 [23]	124 [56]	17 [432]	12 [254]	17 [432]	12 [254]
700		35 [132]	30 [113]	70 [32]	151 [68]	18 3/4 [476]	14 [254]	18 3/4 [476]	14 [254]
800		50 [189]	40 [151]	100 [45]	180 [82]	21 1/2 [546]	16 [254]	21 1/2 [546]	16 [254]

*100, 200, 300 AND 400 ARE STANDARD SUBWAY MODEL SIZES.

ENGINEERING SPECIFICATIONS: ACID RESISTANT COATED INTERIOR AND EXTERIOR FINISH
BRONZE CLEANOUT PLUG, REMOVABLE PRESSURE EQUALIZING/FLOW DIFFUSING INLET
VISIBLE DOUBLE WALL TRAP SEAL

ZURN GREASE INTERCEPTOR


NOTE:

NOTE: CASH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. THESE SYSTEMS HAVE FOR MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL, MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. UL LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.


MANUFACTURER CLEARANCE SPECIFICATIONS:

DO NOT STORE BOXES ON THE TOP OF COOLER OR FREEZER. STORED OBJECTS WILL OBSTRUCT AIR FLOW AND CAUSE VENTILATION PROBLEMS FOR THE REFRIGERATION SYSTEMS.

24\"/>



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL



NORLAKE WALK-IN 4' X 5' OR 4' X 6' REFRIGERATOR OR FREEZER WITH FACE THROUGH WALL TYPICAL ELEVATION DETAIL

ICE CUBER ON S-400 BIN
 COOLED, WATER-COOLED, REMOTE.
 ELECTRICAL SPECIFICATIONS
 5/60/1 20 AMP FUSE MIN.
 12.8 AMPS, WATER-COOLED = 11.9 AMPS
 REMOTE = 9.6 AMPS
 DIRECT OR PER LOCAL CODE
 1/1 ALSO AVAILABLE, SEE MANUFACTURER.
 PLUMBING SPECIFICATIONS
 1) F.P.T. INLET, 1/2" (1.27cm) F.P.T. DRAIN
 3/4" (1.91cm) BIN DRAIN
 2) WATER CONDENSER INLET (WATER-COOLED UNIT)
 WATER CONDENSER OUTLET (WATER-COOLED UNIT)
 APPROVED U.L. #SA-4027/CSA LISTED

NITOWOC ICE CUBER

SIZES IN INCHES [mm]			
E	F	G	
[184]	20 3/8 [518]	9 7/8	[251]
[206]	21 3/4 [552]	11 7/8	[302]
[210]	25 1/8 [638]	14	[356]
[238]	27 1/8 [689]	16 3/4	[425]
[298]	30 [762]	17 1/4	[438]
[318]	32 1/4 [819]	19 7/8	[505]
[362]	34 1/8 [867]	22 1/2	[572]
[406]	36 [914]	24 1/2	[622]

STEEL, INTERNAL AIR RELIEF BYPASS.
 E. FIXED BOTTOM OUTLET BAFFLE.

DR

**TUSCANY II DEC
 BACK-UP SHEET**

REVISION:	BY	DATE
UPDATED ELECTRICAL SPECS ON REACH-INS	PMR	6/10/09

DATE:
 10-31-08

DESIGNED BY:
 PATRICK ROSE

DRAWN BY: REVIEWED BY:
 PMR PMR

SCALE: NOT TO SCALE

SHEET #.

NOTE: CASH DOOR SECTION REQUIRES SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. THESE SYSTEMS HAVE FOR MOTORS THAT REQUIRE SEPARATE 115/60/1 HOOK UP AND DRAWING 2.3 AMPS. ABOVE SPECIFICATIONS FOR CEILING MOUNT SYSTEMS AND INDOOR USE ONLY. WALL, MOUNT AND REMOTE COMPRESSORS AVAILABLE. SEE MANUFACTURER FOR DETAILS. ALL TO BE DIRECT WIRE. NSF APPROVED. UL LISTING #E-486142 (REPORT #48). E.T.L. APPROVED. CSA FILE 18542-24.

MANUFACTURER CLEARANCE SPECIFICATIONS:

DO NOT STORE BOXES ON THE TOP OF COOLER OR FREEZER. STORED OBJECTS WILL OBSTRUCT AIR FLOW AND CAUSE VENTILATION PROBLEMS FOR THE REFRIGERATION SYSTEMS.

24\"/>

STORE MUST BE CONSTRUCTED AS DESIGNED IN THESE FLOOR PLANS SUBJECT TO FEDERAL, STATE AND LOCAL LAWS. RECIPIENT IS RESPONSIBLE FOR ENSURING COMPLIANCE WITH ALL LAWS. IF MODIFICATIONS ARE NECESSARY, PLEASE CONTACT DAYS STORE DESIGN DEPARTMENT FOR WRITTEN APPROVAL OF THE REQUIRED CHANGES.

THIS DRAWING IS FURNISHED BY DOCTORS ASSOCIATES INC. (DAP) DORA SUBWAY. RECIPIENT MUST DETERMINE IF THIS DRAWING MUST BE SUBMITTED TO A LICENSED ARCHITECT OR SIMILAR PROFESSIONAL UNDER FEDERAL, STATE OR LOCAL LAW. ANY CHANGES MUST BE APPROVED BY DAI.

DO NOT SCALE DRAWING. WRITTEN DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS. AND SHALL BE VERIFIED IN THE FIELD BY THE GENERAL CONTRACTOR AND/OR FRANCHISEE. ANY DISCREPANCIES OR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAD NOT BEEN RECEIVED BY DAYS STORE DESIGN DEPARTMENT.

THE GENERAL CONTRACTOR AND EACH SUB-CONTRACTOR SHALL MAKE HIS OWN INSPECTIONS AND MEASUREMENTS. DAI AND SUBWAY SHALL NOT BE HELD RESPONSIBLE FOR THE ACCURACY OF DIMENSIONS AND FOR ERRORS AND OMISSIONS IN THE DRAWINGS IF WRITTEN CONFIRMATION HAD NOT BEEN RECEIVED BY DAYS STORE DESIGN DEPARTMENT.

THIS DRAWING AND THE INFORMATIONAL CONTENT HEREOF IS THE CONFIDENTIAL PROPERTY OF DAI AND IS PROVIDED SOLELY FOR THE USE OF AUTHORIZED FRANCHISEES, THEIR AGENTS AND CONTRACTORS. RECIPIENT AGREES NOT TO REPRODUCE, COPY, USE OR TRANSMIT THIS DRAWING AND ITS INFORMATIONAL CONTENT, IN WHOLE OR IN PART, OR TO ALLOW SUCH ACTION FOR ANY PURPOSE, WITHOUT THE WRITTEN PERMISSION OF DAI. EXCEPT WITH THE WRITTEN PERMISSION OF DAI, RECIPIENT SHALL NOT BE HELD RESPONSIBLE FOR ANY CHANGES OR MODIFICATIONS TO THIS DRAWING. RECIPIENT AGREES TO SURRENDER THIS DRAWING AND ANY PERMITTED COPIES HEREON UPON DEMAND.

SUBWAY

WORLD HEADQUARTERS

(203) 877-4281

325 BIC DRIVE

MILFORD, CT 06461

TUSCANY II DECOR

BACK-UP SHEET

REVISION:	BY	DATE
UPDATED ELECTRICAL SPECS ON REACHINS	PMR	6/009

DATE: 10-31-08

DESIGNED BY: PATRICK ROSE

DRAWN BY: PMR	REVIEWED BY: PMR
---------------	------------------

SCALE: NOT TO SCALE

SHEET #:

3820104

PRINTED 4/8/2010