



WALL FINISH PLAN

SECTION 1007
ACCESSIBLE MEANS OF EGRESS

1007.1 ACCESSIBLE MEANS OF EGRESS REQUIRED.

ACCESSIBLE MEANS OF EGRESS SHALL COMPLY WITH THIS SECTION. ACCESSIBLE SPACES SHALL BE PROVIDED WITH NOT LESS THAN ONE ACCESSIBLE MEANS OF EGRESS. WHERE MORE THAN ONE MEANS OF EGRESS IS REQUIRED BY SECTION 1015.1 OR 1019.1 FROM ANY ACCESSIBLE SPACE, EACH ACCESSIBLE PORTION OF THE SPACE SHALL BE SERVED BY ACCESSIBLE MEANS OF EGRESS IN AT LEAST THE SAME NUMBER AS REQUIRED BY SECTION 1015.1 OR 1019.1. IN ADDITION TO THE REQUIREMENTS OF THIS CHAPTER, MEANS OF EGRESS, WHICH PROVIDE ACCESS TO, OR EGRESS FROM, BUILDINGS FOR PERSONS WITH DISABILITIES, SHALL ALSO COMPLY WITH THE REQUIREMENTS OF CHAPTER 11A OR 11B, AS APPLICABLE.

1011.3 TACTILE EXIT SIGNS.

FOR THE PURPOSE OF SECTION 1011.3, THE TERM "TACTILE EXIT SIGNS" SHALL MEAN THOSE REQUIRED SIGNS THAT COMPLY WITH SECTION 1117B.5.1, ITEM 1. TACTILE EXIT SIGNS SHALL BE REQUIRED AT ALL THE FOLLOWING LOCATIONS:

1. EACH GRADE LEVEL EXTERIOR DOOR SHALL BE IDENTIFIED BY A TACTILE EXIT SIGN WITH THE WORD "EXIT."

2. EACH EXIT DOOR THAT LEADS DIRECTLY TO A GRADE-LEVEL EXTERIOR EXIT BY MEANS OF A STAIRWAY OR RAMP SHALL BE IDENTIFIED BY A TACTILE EXIT SIGN WITH THE FOLLOWING WORDS AS APPROPRIATE:

- A. "EXIT STAIR DOWN"
- B. "EXIT RAMP DOWN"
- C. "EXIT STAIR UP"
- D. "EXIT RAMP UP"

3. EACH EXIT DOOR THAT LEADS DIRECTLY TO A GRADE-LEVEL EXTERIOR EXIT BY MEANS OF AN EXIT ENCLOSURE THAT DOES NOT UTILIZE A STAIR OR RAMP, OR BY MEANS OF AN EXIT PASSAGEWAY, SHALL BE IDENTIFIED BY A TACTILE EXIT SIGN WITH THE WORDS "EXIT ROUTE."

4. EACH EXIT ACCESS DOOR FROM AN INTERIOR ROOM OR AREA THAT IS REQUIRED TO HAVE A VISUAL EXIT SIGN, SHALL BE IDENTIFIED BY A TACTILE EXIT SIGN WITH THE WORDS, "EXIT ROUTE."

5. EACH EXIT DOOR THROUGH A HORIZONTAL EXIT SHALL BE IDENTIFIED BY A TACTILE EXIT SIGN WITH THE WORDS "TO EXIT."

WALL FINISH LEGEND (TUSCANY II DECOR)

*SEE TUSCANY II BACK-UP SHEET 1 OF 4 AND 2 OF 4 FOR PROPER INSTALLATION OF WALLFINISHES IN CUSTOMER AND SERVICE AREAS.
(SEE TUSCANY SUPPLEMENTAL TILE BACK-UP SHEET WHEN APPLICABLE)

SYMBOL	DESCRIPTION	MANUFACTURER	SUPPLY	INST.	NOTES:
	SUBWAY MURAL	SINGLO FABRICS	D.A.I.	G.C.	VINYL WALLCOVERING/UPPER CHAIR RAIL MOLDING AND QUENTIN OR BUTTERNUT BRICK WALLCOVERING AS REQUIRED
	TUSCAN STUCCO WALLCOVERING	SINGLO FABRICS	D.A.I.	G.C.	VINYL WALLCOVERING/WITH LOWER CHAIR RAIL MOLDING
	WINDOW FRAME			G.C.	G.C. PAINT SHERVIN WILLIAMS #SW6356 COPPER MOUNTAIN. CITYSCAPE MURAL, UPPER CHAIR RAIL MOLDING AND QUENTIN OR BUTTERNUT BRICK WALLCOVERING AS REQUIRED
	TUSCAN STUCCO WALLCOVERING	SINGLO FABRICS	D.A.I.	G.C.	VINYL WALLCOVERING/WITH LOWER CHAIR RAIL MOLDING
	RED WALL COVERING	SINGLO FABRICS	D.A.I.	G.C.	VINYL WALLCOVERING
	TUSCAN STUCCO WALLCOVERING	SINGLO FABRICS	D.A.I.	G.C.	VINYL WALLCOVERING/WITH LOWER CHAIR RAIL MOLDING
	WALL CAPS		G.C.	G.C.	G.C. HARDWOOD PLANK (STAINED MINWAX #235 CHERRY AND POLYURETHANED WITH MINWAX FAST DRYING CLEAR SATIN)
	FRP OR PAINTED WALLS	MARLITE/G.C.	DAL/GC	G.C.	WHITE FRP PANELS OR OFF-WHITE SEMI-GLOSS PAINT
	FIBERGLASS REINFORCED POLYESTER PANELS (FRP)	MARLITE	D.A.I.	G.C.	FRP PANELS - WATER RESISTANT COVERING. WHITE OR *ALMOND (*ALMOND OPTION ONLY IF PERMITTED BY HEALTH/BUILDING CODE)
	RESTROOM: TILED WALLS	CROSSVILLE/ DAL-TILE	G.C.	G.C.	OPTION 1: COLORBLOX STONE FLOOR TILE MOUNTED FLOOR TO CEILING. CHOOSE 1 OR MORE OF THE FOLLOWING: A1153 CLAY, A1154 GREEN, A1156 WHEAT. OPTION 2: DAL-TILE K165 ALMOND 4 1/4" X 4 1/4" CERAMIC TILE FLOOR TO CEILING.
	MOSAIC TILE (RIGHT)	IMAGINE TILE	D.A.I.	G.C.	4 1/4" X 4 1/4" CERAMIC TILE. VEGETABLE GRAPHIC TILES FRAMED BY 1A (LIGHT CHERRY). SEE TUSCANY II SUPPLEMENTAL TILE BACK-UP SHEET FOR INSTALLATION.
	MOSAIC TILE (LEFT)	IMAGINE TILE	D.A.I.	G.C.	4 1/4" X 4 1/4" CERAMIC TILE. VEGETABLE GRAPHIC TILES FRAMED BY 1A (LIGHT CHERRY). SEE TUSCANY II SUPPLEMENTAL TILE BACK-UP SHEET FOR INSTALLATION.
	CERAMIC TILE	IMAGINE TILE	G.C.	G.C.	4 1/4" X 4 1/4" CERAMIC TILE. COLOR: 1A (LIGHT CHERRY). SEE TUSCANY II SUPPLEMENTAL TILE BACK-UP SHEET FOR INSTALLATION.
	GRIMALDI CERAMIC TILE RESTROOM/SERVICE AREAS	ASSOCIATED ACQ/ INTERNATIONAL LTD.	G.C.	G.C.	8" X 8" CERAMIC TILE. COLOR: CURRY (YELLOW). ITEM# C212005061. 8" X 8" CERAMIC TILE. COLOR: MUSGO (GREEN). ITEM# C212005051. GROUT COLOR: #17 BUTTER CREAM NON SANDED.

NOTE: ALL WOOD INTERIOR DOORS, UPPER & LOWER MOLDING & CROWN MOLDING TO BE STAINED W/ MINWAX #235 CHERRY AND POLYURETHANED W/ MINWAX FAST DRYING CLEAR SATIN.

NOTE: F.R.P. SHOULD BE TO CEILING HEIGHT IN BACKROOM, BUT MUST BE A MINIMUM OF 8'-0" ABOVE FINISHED FLOOR. F.R.P. IN RESTROOMS MUST BE FLOOR TO CEILING.

TUSCANY II DECOR CALCULATIONS

NOTE: THE SUBWAY STORE DESIGN DEPARTMENT WILL NOT ACCEPT RESPONSIBILITY FOR ANY INACCURACIES. THE CALCULATIONS PROVIDED BELOW MUST BE VERIFIED BY THE G.C. AND FRANCHISE OWNER BEFORE ANY ORDER FOR THESE MATERIALS IS ACCEPTED AND PLACED.

QUANTITIES	CALCULATION WORKSHEET
CUSTOMER AREA	
1) <36 > YARDS CITYSCAPE MURAL	1) M/TS + S/M + 10% DIVIDED BY 3.
2) <47 > YARDS OF TUSCAN STUCCO WALL COVERING	2) M/TS + T/S + R/TS 10% DIVIDED BY 3
3) <108 > FEET OF UPPER DECORATIVE MOLDING	3) M/TS + S/M + 10%
4) <41 > FEET OF LOWER CHAIR RAIL MOLDING	4) M/TS + T/S + R/TS 10%
5) <19 > YARDS OF QUENTIN WALLCOVERING (NON-TEALAR) OR OPTIONAL BUTTERNUT BRICK WALLCOVERING ABOVE CITYSCAPE MURAL.	5) (CEILING HEIGHT - 7'-6") X (M/TS + S/M + (Q/WC OR B/T IN CUSTOMER AREA ONLY)) + 5% DIVIDED BY 12
6) <157 > FEET OF HARDWOOD CROWN MOLDING (AT CORNER WHERE WALL AND CEILING MEET)	6) M/TS + S/M + R/TS (+ W/TS IF WINDOWS NOT TO CEILING) + 10%.
7) <11 > FEET OF HARDWOOD CROWN MOLDING (FINISH CAP ON STRIP LIGHTING SHELF)	7) TOTAL LENGTH OF WALLS WHERE FLUORESCENT STRIP LIGHTING TO BE INSTALLED + 10%
8) <18 > YARDS OF RED WALL COVERING	8) HEIGHT FROM TOP OF TUSCAN STUCCO WALL COVERING TO CEILING (36" AFF.) X R/TS + 5% DIVIDED BY 12
9) <11 > YARDS OF QUENTIN WALLCOVERING (WITH TEALAR COATING) (FOR 48" HIGH BANQUETTE WALL ONLY)	9) Q/WC + 10% DIVIDED BY 3. (CUSTOMER AREA ONLY)
SERVICE AREA	
10) <11 > 4' X 12' SHEETS FONT-HILL PEAR LAMINATE	10) FP/L + 5% DIVIDED BY 12
11) <11 > 12' T-MOLDING STRIPS	11) FP/L ON 36" HIGH WALLS X 2) + (FP/L ON 48" HIGH WALLS X 3) + 5% DIVIDED BY 12
12) <11 > YARDS OF BUTTERNUT BRICK TEXTURED WALL COVERING	12) CEILING HEIGHT X B/T + 5% DIVIDED BY 12
13) <11 > YARDS OF QUENTIN WALL COVERING (WITH TEALAR COATING)	13) CEILING HEIGHT X Q/WC + 5% DIVIDED BY 12
14) <1 > RIGHT < LEFT VEGETABLE MOSAIC TILE	14) TOTAL LENGTH OF CUSTOMER SIDE OF HEADERWALL(S) OVER SERVICE AREA + 5%.
15) <11 > (OPTIONAL) FEET OF COPPER CORNICE TRIMS	
16) <11 > 4' X 12' SHEETS FONT-HILL PEAR LAMINATE (OPTIONAL: FOR SOFFIT APPLICATION)	
BACKROOM	
17) <18 > MARLITE F.R.P. WHITE (ALMOND OPTIONAL IF PERMITTED BY HEALTH/BUILDING CODE)	17) W/R + 5% DIVIDED BY 4
18) <27 > PVC DIVISION MOLDING	18) PANEL COUNT FROM #17 28. LESS 1
19) <13 > PVC INSIDE CORNER	19) COUNT ALL INSIDE CORNERS WHERE W/R MEET
20) <10 > PVC OUTSIDE CORNER	20) COUNT ALL OUTSIDE CORNERS WHERE W/R MEET
21) <16 > PVC CAP MOLDING	21) COUNT ALL EDGES WHERE W/R BEGINS & ENDS & DOORWAYS.
PUBLIC ACCESS RESTROOMS	
22) <11 > MARLITE F.R.P. ALMOND	22) A/FRP + 5% DIVIDED BY 4
23) <11 > PVC DIVISION MOLDING	23) PANEL COUNT FROM #22 N/A. LESS 1
24) <11 > PVC INSIDE CORNER	24) COUNT ALL INSIDE CORNERS WHERE A/FRP MEET
25) <11 > PVC OUTSIDE CORNER	25) COUNT ALL OUTSIDE CORNERS WHERE A/FRP MEET
26) <11 > PVC CAP MOLDING	26) COUNT ALL EDGES WHERE A/FRP BEGINS & ENDS & DOORWAYS.
27) <11 > YARDS OF TUSCAN STUCCO IN RESTROOMS	27) HEIGHT FROM TOP OF WALL TILE TO CEILING (48"-52" AFF.) X RR/2 + 5% DIVIDED BY 8.

* CALCULATIONS ARE FOR FONT-HILL PEAR LAMINATE AND ALUMINUM T-MOLDING APPLIED TO 36" AND 48" HIGH WALLS. LAMINATE AND T-MOLDING, WHEN AFFIXED DIRECTLY TO DUKE FRONT COUNTER, IS SHIPPED READY TO INSTALL BY DUKE MANUFACTURING.

NOTE: THESE CALCULATIONS DO NOT INCLUDE THE MATERIALS NEEDED TO DECOR THE AREA ABOVE OR BELOW THE WINDOWS.

P.E.
INCORPORATED
PASQUINI
ENGINEERING

908 H Street Suite 300
Bakersfield, Ca. 93304
Telephone: (661)-328-9600
Fax: (661)-328-9030

NO.	DATE

SUBWAY
STORE 2502
950 FIFTH AVE.
SAN DIEGO, CA 92101

THESE PLANS ARE NOT FOR CONSTRUCTION UNLESS A "WET STAMP & SIGNATURE" FROM BOTH THE ENGINEER OF RECORD AND A APPROVAL STAMP WITH A "WET STAMP & SIGNATURE" FROM THE LOCAL GOVERNING AGENCY ARE PRESENT.

DWG. BY	J.P.
CHK'D BY	
DATE	8/11/2010
JOB NO.	6196
FILE NO.	619622

EXP. 12/31/10

SHEET	3
-------	---

PRINTED 11/17/2010